

19" Rack-mounted PLC splitter

Features:

- Low insertion loss, Low PDL and High reliability
- High return loss and Good repeatability
- Wide wavelength range
- Excellent channel-to-channel uniformity



Applications:

- LAN, WAN and Metro Networks
- FTTH project & FTTX Deployments
- CATV System
- GPON, EPON
- Fiber Optic Test Equipment
- Data-base Transmit Broadband Net

Encapsulation Size

Item	1x2	1x4	1x8	1x16	1x32	1x64
Length*Width*Height (mm)	482*160*44.5					482*160*89
Item	2x2	2x4	2x8	2x16	2x32	2x64
Length*Width*Height (mm)	482*160*44.5					482*160*89

Technical Specs for PLC Splitter with Connector

Item	1x2	1x4	1x8	1x16	1x32	1x64	1x128
Fiber Type	G.657.A						
Working Wavelength	1260nm~1650nm						
Standard Insertion Loss (dB)	≤4.2	≤7.6	≤10.7	≤14.0	≤17.2	≤20.8	≤24.0
P- Grade Insertion Loss (dB)	≤4.0	≤7.4	≤10.5	≤13.8	≤17.0	≤20.4	≤23.7
Uniformity (dB)	≤0.6	≤0.8	≤0.8	≤1.0	≤1.5	≤2.0	≤2.0
PDL (dB)	≤0.2	≤0.2	≤0.3	≤0.3	≤0.3	≤0.4	≤0.5
Wavelength Dependent Loss (dB)	≤0.6	≤0.8	≤0.8	≤1.0	≤1.5	≤2.0	≤2.0
Return Loss (dB)	≥50						

Directivity (dB)	≥55
Operating Temp. Range	-40℃~ +85℃
Note: The above parameter is for Splitter with connector. If w/o connector, insertion loss will reduce by 0.2dB.	

Item	2x2	2x4	2x8	2x16	2x32	2x64	2x128
Fiber Type	G.657.A						
Working Wavelength	1260nm~1650nm						
Standard Insertion Loss (dB)	≤4.4	≤8.0	≤11.0	≤14.6	≤17.8	≤21.0	≤24.4
P- Grade Insertion Loss (dB)	≤4.2	≤7.7	≤10.8	≤14.1	≤17.4	≤20.7	≤24.0
Uniformity (dB)	≤0.8	≤1.0	≤1.2	≤1.5	≤1.8	≤2.0	≤3.0
PDL (dB)	≤0.2	≤0.2	≤0.3	≤0.3	≤0.3	≤0.4	≤0.5
Wavelength Dependent Loss (dB)	≤0.8	≤1.0	≤1.2	≤1.5	≤1.8	≤2.0	≤3.0
Return Loss (dB)	≥50						
Directivity (dB)	≥55						
Operating Temp. Range	-40℃~ +85℃						
Note: The above parameter is for Splitter with connector. If w/o connector, insertion loss will reduce by 0.2dB.							

Ordering Info

	Port	Fiber	Input Pigtail	Input Connector	Input Pigtail Length	Output Pigtail	Output Connector	Output Pigtail Length
PLC	102=1x2	1=G657A	1=250um	NE=None	0=0.5m	1=250um	NE=None	0=0.5m
	104=1x4	2=G652D	Bare Fiber	SU=SC/UPC	1=1m	Bare Fiber	SU=SC/UPC	1=1m
	108=1x8	SP=Special	2=900um	SA=SC/APC	2=1.5m	2=900um	SA=SC/APC	2=1.5m
	116=1x16		tight buffer	LU=LC/UPC	3=2m	tight buffer	LU=LC/UPC	3=2m
	132=1x32		3=900um	LA=LC/APC	4=3m	3=900um	LA=LC/APC	4=3m
	164=1x64		loose	FU=FC/UPC	SP=Special	loose	FU=FC/UPC	SP=Special
	128=1x128		tube	FA=FC/APC		tube	FA=FC/APC	
	204=2x4		4=Φ2.0mm	SP=Special	4=Φ2.0mm	SP=Special		
	208=2x8		cable		cable			
	216=2x16		5=Φ3.0mm		5=Φ3.0mm			
	232=2x32		cable		cable			
	264=2x64		SP=Special		SP=Special			